@_maxoutmgmt_

STACK FLUID





3	stack	Recommended for Stacking in 6" Rockwool or 100% Coco 1 Gal units are in mL/gal													
7		CLONE		VEGET	TATIVE		FLOWER								
//		SOAK	week 1	week 2	week 3	week 4	week 1	week 2	week 3	week 4	week 5	week 6	week 7	week 8	flush
mix in order	powersi original	0.5	0.5	0.5	0.5	0.5									
	camg	2	2	2	2	2	2	2	2	2	2	2	2	2	
	base a	10	10	10	10	10	9	9	9	7	7	6	6		
	base b	10	10	10	10	10	9	9	9	8	8	8	8		
	flex						2	2	2	3	3	3	3	3	
	Target PPM 500	1005					990			880		820		220	
$^{\downarrow}$ [Target PPM 700	1407					1386			1232		1148		308	
\prod	Target EC			2.01			1.98			1.76		1.64		0.44	
) D	Target pH	5.5-5.6	5.5-	6.5 (Coco	& Rockv	vool)	5.5-6.5 (Coco & Rockwool)								
							LE	D							
//	Day Temp (°F)		80-84					80-84			80-82			76-78	74-76
	Night Temp (°F)		78-82				78-82			76-80			74-78	70-74	68-72
	RH (%)	65-70					65-70			60-65			53-58	45-50	40-45
	Day VPD (kPa)			1.1-1.2				1.1-1.2			1.3-1.4			1.6-1.7	1.7
	PPFD	100	Increase from 200-500 depending on veg time					Increase from 800, ~5% per day, to reach 1050-1200			1050-1200			700-800	600
	CO ₂ (PPM)	PM) 600					1100-1400			1100-1400			900-1000	800-900	700
$\backslash \backslash$	Substrate EC			<.	5		<8			<5			<3	<3	<1
10	HPS														
/)	Day Temp (°F)		77-81			77-81			77-79			75-77	73-75	71-73	
D)	Night Temp (°F)		75-79				75-79			73-77			71-75	67-71	65-69
5	RH (%)					65-70			60-65			53-58	45-50	40-45	
	Day VPD (kPa)		1.1				1.1			1.2-1.3			1.3-1.4	1.5-1.6	1.5-1.6
	PPFD	100 Increase from 200-500 depending on veg time			Increase from 800, ~7% per day, to reach 950-1100			950-1100			700-850	700-800	600		
	CO ₂ (PPM)	600					1100-1400			1100-1400			900-1000	800-900	700
	Substrate EC		<5				<8			<5			<3	<3	<]

notes

- ·Vegetative Dryback: Do not get water content under 25-30% of field capacity.
- Vegetative EC Stack Point Targets: 4-6 EC at field capacity.
- Generative Dryback: Do not get water content under 40-45% of field capacity.
- Generative EC Stack Point Targets: 6-8 EC at field capacity.
- We advise against stacking (crop steering) if you do not have the correct instruments such as moisture sensors and climate control.
- In Coco, 2mL/gal of CaMg is recommended.
- ·Certain cultivars will not require as much CaMg. Reduce to 1 mL/gal or remove completely.
- ·Use Flow once weekly.
- Do not mix Flow with PowerSi.
- ·Use PowerSi on the days you do not use
- Do not use Flow if you are using beneficial bacteria.
- Foliar PowerSi Original @2-4 mL/gal once weekly.
- LED leaf surface temperature should be 2-5° less than ambient room temperature.
- ·HPS leaf surface temperature should be 1-4° less than ambient room temperature.
- Check apex of the plant, in full light, daily, two hours after lights turn on.